

# MiniBlade Omnidirectional Wi-Fi 6E, CBRS 5G Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

710599, 710629, 710630, 710631



## Description


Slim and compact cellular antenna that delivers reliable connectivity.

## Technologies

- 2.4 / 3.5 / 5 / 6GHz
- Wi-Fi 6E
- Bluetooth®

## Features

- 5G ready
- Easy installations with adhesive mount on glass or non-conductive surface
- Slim and flexible design made it suitable for curved surface mounting



## MiniBlade Omnidirectional Wi-Fi 6E, CBRS 5G Antenna

### Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

MiniBlade by Smarteq, a PCTEL company, is an adhesive mounted omnidirectional ultra-wideband antenna capable of supporting radio systems operating in the 2400 to 7200MHz spectrum. Wi-Fi 6E, Bluetooth®, V2X and 5G ready, the MiniBlade antenna is the perfect choice for applications such as indoor Wi-Fi coverage, internet onboard buses, EV-chargers, Wi-Fi zones, and Wi-Fi supported devices. Its superior RF performance enables high connectivity and throughput.

#### Features

- Wi-Fi 6E, Bluetooth®, V2X and 5G ready
- 2400 - 7200MHz
- Easy installations with adhesive mount on glass or non-conductive surface
- Slim and flexible design made it suitable for curved surface mounting
- IATF 16949

#### Applications

- Off-Highway Vehicle (OHV)
- ECU/Gateway
- Smart Metering
- Smart City
- EV-chargers
- Industrial IoT

#### Certifications



## SPECIFICATIONS

# MiniBlade Omnidirectional Wi-Fi 6E, CBRS 5G Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

### Standard Configurations

Model	Cable	Cable Length	Connector	Housing Color
710599	RG316	1.5m	SMA-male	Black
710629	RG316	0.5m	SMA-male	Black
710630	RG316	0.2m	SMA-male	Black
710631	RG316	0.5m	RP SMA-male	Black

### Electrical Specifications – RF Antennas (All Models)

Frequency Ranges	VSWR	Max. 3D Gain	Efficiency	Nominal Impedance	Polarization	Radiation Pattern
2400 - 2485 MHz	2:1	3.8dBi	79%	50Ω	Linear	Omnidirectional
3400 - 3800 MHz	2:1	5dBi	71%			
4900 - 5050 MHz	2:1	7dBi	64%			
5925 - 7125 MHz	3:1	5dBi	33%			

### Mechanical and Environmental Specifications (All Models)

#### Physical

Dimensions (L x W x H)	55.6 x 23.6 x 6.6mm (incl. 1.1mm 3M adhesive)
Weight	~ 35g (incl. 1.5m cable with SMA connector)
Material	Dryflex, FR4
Operating / Storage Temperature	-40°C to +85°C
IP Class	IATF 16949

### Extension Cables

Part Number	Cable Length	Connector	Gender	Color
<b>LL58 Cable</b>				
201417-1	3m	SMA	Female/Male	White
201417-2	5m	SMA	Female/Male	White
201417-3	10m	SMA	Female/Male	White
201417-7	5m	SMA	Female/Male	Black
<b>Low Loss Cable</b>				
707220	3m	SMA	Female/Male	Black
710298	5m	SMA	Female/Male	Black
201417-3	10m	SMA	Female/Male	Black

\* RF data with the antenna mounted on plastic 5mm thick and 20cm long cable

**CONTACT US**

**For more information about  
this product contact your  
sales representative or visit  
> [www.stepglobal.com](http://www.stepglobal.com)**

**Engineered Solutions for Real Time  
Management of Mobile Assets**

Step Global has been providing innovative GPS & RFID solutions for our customers for over 20 years. We supply a broad range of technology products from globally recognised manufacturers. We provide Antennas, Asset Tracking, Precision Timing, GNSS Signal Distribution and Simulation and more, to satisfy all your assets tracking and monitoring needs.



[www.stepglobal.com](http://www.stepglobal.com)  
+61 3 9551 7334  
[sales@stepglobal.com](mailto:sales@stepglobal.com)

1 Arco Lane  
Heatherton, Vic  
3202 Australia