



# Multiband MIMO Antennas Mobile & Infrastructure

Multiband LTE/5G Pg 2

---

Multiband WiFi & GNSS Pg 3

---

Multiband LTE/5G  
& WiFi Pg 4

---

Multiband  
Special Networks Pg 5

---

Multiband LTE/5G  
& GNSS Pg 7

---

Multiband LTE/5G  
Wifi & GNSS Pg 11

**MobileMark**  
antenna solutions

**MAXTENA**  
WIRELESS INNOVATIONS COMPANY





**PCTEL**

**SANAV**  
San Jose Technology, Inc.

**STEPGLOBAL**




in  [shop.stepglobal.com](https://shop.stepglobal.com)

# Multiband LTE/5G

	<p>PND10-700/2700 (2x LTE MIMO Directional Panel) <b>Cable 1 &amp; 2:</b> 694-960 MHz, 9 dBi &amp; 1710-2750 MHz, 10 dBi Adjustable Pole Mount Dimensions: 38cm x38cm (1.4kg) Configurable cable lengths and connector types</p>
	<p>PNM2-LTE (Wall Mount 2x LTE MIMO Omnidirectional) <b>Cable 1 &amp; 2:</b> 694-960 MHz, 2 dBi &amp; 1710-2750 MHz, 2 dBi Wall Mount Design Dimensions: 14.6cm L x14.6cm W x1.8cm H (0.5kg) Configurable cable lengths and connector types</p>
	<p>4GDPSM (2x LTE) <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi Thru Hole Mount Dimensions: 81.5 OD x 40 H mm (0.14kg) Configurable cable lengths and connector types</p>
	<p>PCTHPDLTE-SF ( M) (2x Global 5G LTE) <b>Cable 1 &amp; 2:</b> 617-960 MHz, 5 dBi &amp; 1710-6000 MHz, 8 dBi Thru hole mount Dimensions: 13.2cm x 9.4 cm Configurable cable lengths and connector types</p>

# Multiband WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number SMWGxxx with MGWGxxx and part number LTMGxxx with MLTMGxxx

<p>LTMG504<sup>(M)</sup> (4xWiFi, 1x GNSS) <b>Cables 1-4:</b> 2.4-2.5 Ghz &amp; 4.9-6 GHz, 5 dBi <b>Cable 5 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 13.9cm Dia. x 6.05 cm H Configurable cable lengths and connector types</p>	
<p>DMG-W15 (1x WiFi, 1x GNSS) <b>Cable 1:</b> 2.4-2.5 &amp; 4.9-6.0 MHz, 2.5 dBi <b>Cable 2 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi gain Thru Hole Mount Dimensions: Thru Hole Mount (7.2 cm Dia. x 3.7 cm H), Mag Mount (9.5 cm Dia. x 4.6 cm H) Configurable cable lengths and connector types</p>	
<p>SMWG-303<sup>(M)</sup> (2xWiFi, GNSS) <b>Cable 1:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 2:</b> 2.1-2.5 &amp; 4.4-6.0 GHz, 5 dBi <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA: 26dB, 5 dBi nominal RHCP Thru Hole Mount Dimensions: 10.7 cm Dia. x 8.1 cm H Configurable cable lengths and connector types</p> <p>SMWG-304<sup>(M)</sup> (2xWiFi, GNSS) <b>Cable 1:</b> 2.4-2.5 GHz, 5 dBi <b>Cable 2:</b> 2.1-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 3 (GNSS) :</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi gain Thru Hole Mount Dimensions: 10.7 cm Dia. x 8.1 cm H Configurable cable lengths and connector types</p> <p>SMWG-410<sup>(M)</sup> (3x WiFi, GNSS) <b>Cable 1:</b> 2.1-2.5 &amp; 4.4-6.0 GHz, 5 dBi <b>Cable 2:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 3:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 4 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA: 26dB, 5 dBi nominal RHCP Thru Hole Mount Dimensions: 10.7 cm Dia. x 8.1 cm H Configurable cable lengths and connector types</p>	

# Multiband LTE/5G & WiFi



PCTHPDLTEMIMO-SF (M) (2x Global 5G LTE, 2x WiFi)

**Cable 1 & 2:** 617-960 MHz, 5 dBi & 1710-6000 MHz, 8 dBi

**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 9 dBi

Thru Hole Mount

Dimensions: 132cm x 9.4 cm

Configurable cable lengths and connector types

PCTHPDLTEWIFI-SF (M) (2x Global 5G LTE, 1x WiFi)

**Cable 1 & 2:** 617-960 MHz, 5 dBi & 1710-6000 MHz, 8 dBi

**Cable 3:** 2.4-2.5 & 4.9-6.0 GHz, 9 dBi


Thru Hole Mount

Dimensions: 132cm x 9.4 cm

Configurable cable lengths and connector types

# Multiband Special Networks Inc. UHF, DSRC, V-V2X, Iridium

(M) Magnetic mount option also available with side entry cables. Replace part number SMWGxxx with MGWGxxx

	<p>LLPG304 (1x LTE/5G, 1x UHF, 1x GNSS)  <b>Cable 1 (Global LTE):</b> 694-4200 MHz  <b>Cable 2 (UHF):</b> 450-470 MHz  <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi gain            Thru Hole Mount            Dimensions: 22.8cm L x 8.9cm W x 3.18cm H            Configurable cable lengths and connector types</p>
	<p>SMWG-310<sup>(M)</sup> (1x UHF, 1x WiFi, 1x GNSS)  <b>Cable 1:</b> 450-470 MHz, 2 dBi  <b>Cable 2:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi  <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi gain            Thru Hole mount            Dimensions: 22.8cm L x 8.9cm W x 3.18cm H            Configurable cable lengths and connector types</p> <p>SMWG-313<sup>(M)</sup> (2x DSRC, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 5.8-6.0 GHz, 7 dBi  <b>Cable 3 (GNSS) :</b> 1561, 1575, &amp; 1602 MHz,            LNA: 26dB, 5 dBi nominal RHCP            Thru Hole mount            Dimensions: 22.8cm L x 8.9cm W x 3.18cm H            Configurable cable lengths and connector types</p> <p>SMWG-314<sup>(M)</sup> (1x LTE/5G, 1x DSRC, 1x GNSS)  <b>Cable 1:</b> 694-960 MHz, 3 dBi &amp; 1710-3700 MHz, 4 dBi  <b>Cable 2:</b> 5.8-6.0 GHz, 7 dBi  <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi gain            Thru hole mount            Dimensions: 22.8cm L x 8.9cm W x 3.18cm H            Configurable cable lengths and connector types</p>
	<p>MXFG-5900 (2x DSRC or C-V2X, 1x GNSS)  <b>Cable 1&amp;2:</b> 5850-5925 MHz, 4 dBi gain (8 dBi peak)  <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB,            5 dBi nominal RHCP            Thru Hole Mount            Dimensions: 19cm x 5.7 cm x 6.4cm            Configurable cable lengths and connector types</p>

# Multiband Special Networks Inc. UHF, DSRC, V-V2X, Iridium

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx



LTMG503<sup>(M)</sup> (2x LTE, 1x WiFi, 1x GNSS, 1x Iridium)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-2170 MHz, 4 dBi

**Cable 3:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 4 (IRIDIUM):** 1616-1626.5 MHz, 3.5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 14.0cm Dia. x 6.04cm H

Configurable cable lengths and connector types

LTMG507<sup>(M)</sup> (2x LTE, 1x WiFi, 1x GNSS, 1x Iridium<sup>®</sup>)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4 dBi

**Cable 3:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 4 (IRIDIUM):** 1616-1626.5 MHz, 3.5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 14.0cm Dia. x 6.04cm H

Configurable cable lengths and connector types

# Multiband LTE/5G & GNSS

## CVWG-LTE (LTE, GNSS)

**Cable 1:** 694-960 & 2100-2700 MHz, 2.5 dBi

**Cable 2 (GNSS):** 1561, 1575, & 1602 MHz, 26 LNA, 5 dBi

Thru Hole Mount

Dimensions: 14 cm L x 4 cm W

Configurable cable lengths and connector types



## LMWG201 (LTE, GNSS)

**Cable 1:** 695-960 (Unity) & 1710-2700 MHz (3 dBi)

**Cable 2 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 8.9 cm D x 3.8 cm H

Configurable cable lengths and connector types

## LMWG202 (LTE/5G, GNSS)

**Cable 1:** 695-960 (Unity) & 1710-3700 MHz (3 dBi)

**Cable 2 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 8.9 cm D x 3.8 cm H

Configurable cable lengths and connector types



## LMWG203 (1x Global 5G LTE, GNSS)

**Cable 1:** 695-960 (Unity) & 1710-6000 MHz (3-5 dBi)

**Cable 2 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 8.9 cm D x 3.8 cm H

Configurable cable lengths and connector types

## LLPG203 (LTE/5G, GNSS)

**Cable 1:** 694-960 MHz & 1710-3700 MHz, -1 dBi to 4 dBi

**Cable 2 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 22.8cm L x 8.9cm W x 3.18cm H

Configurable cable lengths and connector types



## LLPG302 (2x LTE/5G, GNSS)

**Cable 1 & 2:** 694-3700 MHz, 0 dBi - 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 22.8cm L x 8.9cm W x 3.18cm H

Configurable cable lengths and connector types

# Multiband LTE/5G & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx etc

## LTBG301 (2X LTE, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-2700 MHz, 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 19cm L x 3.8 cm W x 10cm H

Configurable cable lengths and connector types



## LTBG302 (2X LTE/5G, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-4200 MHz, 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 19cm L x 3.8 cm W x 10cm H

Configurable cable lengths and connector types

## LTM940 : 4xLTE/5G, 1xGPS

**Cable 1-4:** 694-960 MHz, 2 dBi & 1710-3700 MHz, 5 dBi

**Cable 5 (GPS):** 1575,

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

## LTMG940<sup>(M)</sup>: (4x LTE, 1x GNSS)

**Cable 1-4:** 694-960 MHz,

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types



## LTMWG940: 4x 5G, 1x GNSS

**Cable 1-4:** 2 dBi & 1710-3700 MHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

## LTMG301<sup>(M)</sup> (2x LTE, 1x GNSS)

**Cable 1 & 2:** 694-960 MHz, 3 dBi & 1710-2170 MHz, 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 1.40 cm Dia. x 6.4 cm H

Configurable cable lengths and connector types

## LTMG302<sup>(M)</sup> (2 X LTE/5G, GNSS)

**Cable 1 & 2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 1.40 cm Dia. x 6.4 cm H

Configurable cable lengths and connector types





# Multiband LTE/5G & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxxx with MLTMGxxxx

LTMG308<sup>(M)</sup> (2 x Global 5G LTE, GNSS)

**Cables 1 & 2:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 4 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 1.40 cm Dia. x 6.4 cm H

Configurable cable lengths and connector types



LTMG506<sup>(M)</sup> (2x LTE, 2x 5G, 1x GNSS)

**Cable 1&2:** 694-960 MHz (3 dBi) 1710-2170 MHz (4 dBi)

**Cable 3 & 4:** 3300 MHz-3800 MHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 1.40 cm Dia. x 6.4 cm H

Configurable cable lengths and connector types

MXFG302: 2x LTE, 1x GNSS

**Cables 1&2:** 694-960 MHz/1710-3700 MHz

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz

Thru Hole Mount

Dimensions: 1.9cm x 5.7 cm x 6.4cm

Configurable cable lengths and connector types



BOA-LCMGPS-PTNF-4LTE (4x LTE/5G, 1x GNSS)

**Cable 1 - 4:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5dB

Collar Mount

Dimensions: 8.26 OD x 90.6 cm H

Configurable cable lengths and connector types



GL4X4-SF-PLK (4x Global 5G LTE, 1x GNSS)

**Cable 1 - 4:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 6 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 26 dB

Thru Hole Mount

Dimensions: 13 cm Dia. x 9.2 cm H

Configurable cable lengths and connector types



GLHPDM3-SF (2x LTE, 1 x GNSS) (-MM for Mag Mount Version)

**Cable 1 & 2:** 698-960 MHz, 2.5 dBi & 1710-2700 MHz, 2.5 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, 26 dB








Mag Mount

Dimensions: 13 cm Dia. x 9.2 cm H

Configurable cable lengths and connector types



# Multiband LTE/5G & GNSS


<p>GNSS4GDPSM (2x LTE, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi  <b>Cable 3 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 25 dB                      Thru Hole Mount                      Dimensions: 81.5mm OD x 40mm H (0.14kg)                      Configurable cable lengths and connector types</p>	
<p>GNSS4GSM (1x LTE, 1x GNSS)  <b>Cable 1:</b> 698-960 MHz, 5 dBi &amp; 1710-2700 MHz, 5 dBi  <b>Cable 2: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 28 dB                      Thru Hole Mount                      Dimensions: 8cm OD x 1.5cm H                      Configurable cable lengths and connector types</p>	
<p>TRP-20INT-3-B (2x Global 5G LTE, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 617-960 MHz, 5 dBi &amp; 1710-6000 MHz, 8 dBi  <b>Cable 3: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimensions: 10.3cm L x 7cm W x 11.9cm H                      Configurable cable lengths and connector types</p>	
<p>HDGLDLTE-LFF (2x LTE, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi  <b>Cable 3: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimensions: 25.5cm L x 10.0cm W x 5.58cm H                      Configurable cable lengths and connector types</p>	
<p>GLHPDLTE-LTB (2x Global 5G LTE, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 617-960 MHz, 4 dBi &amp; 1710-6000 MHz, 8 dBi  <b>Cable 3: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimensions: 10.3cm W x 8.8cm L                      Configurable cable lengths and connector types</p>	
<p>Cobra-LTE700 (2x LTE, 1x GPS)  <b>Cable 1 &amp; 2:</b> 698-960 MHz, 4 dBi &amp; 1710-2200 MHz, 4 dBi  <b>Cable 3: (GPS):</b> 1575 MHz, 34 dB                      Thru Hole Mount                      Dimensions: 16.6cm W x 20cm L x 8.8cm H                      Configurable cable lengths and connector types</p>	
<p>Maxwave 4x4 Train Antenna (4x 700 to 6000 MHz, 1x GNSS)  <b>Cable 1 to 4:</b> 698-6000 MHz, 9 dBi  <b>Cable 5: (GNSS):</b> 1575, &amp; 1602 MHz, 30 dB                      Thru Hole Mount                      Dimensions: 8.1cm H x 70.2cm W x 87cm L                      Configurable cable lengths and connector types</p>	

# Multiband LTE/5G, WiFi & GNSS

	<p>CVWG402 (2x LTE, 1x WiFi, 1x GNSS) <b>Cable 1 &amp; 2:</b> 694-960 MHz, 3 dBi &amp; 1710-2750 MHz, 4 dBi <b>Cable 3:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 4 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi Tape mounting Dimensions: 17.8cm L x 5.1cm W x 1.9cm H Configurable cable lengths and connector types</p>
	<p>LLPG402 (2x LTE/5G, WiFi, GNSS) <b>Cable 1 &amp; Cable 2:</b> 694-3700 MHz, 0 dBi to 4 dBi <b>Cable 3:</b> 2400-2500 MHz, 4 dBi &amp; 5000-6000 MHz, 5 dBi <b>Cable 4 (GNSS):</b> 1561, 1575, &amp; 1602, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p> <p>LLPG403 (LTE/5G, 2X WIFI, GNSS) <b>Cable 1:</b> 694-3700 MHz, -1 dBi to 4 dBi <b>Cables 2 &amp; 3:</b> 2400-2500 MHz, 4 dBi &amp; 5000-6000 MHz, 5 dBi <b>Cable 4 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p> <p>LLPG502 (2x LTE/5G, 2x WiFi, GNSS) <b>Cable 1 &amp; Cable 2:</b> 694-3700 MHz, 0 dBi to 4 dBi <b>Cable 3 &amp; 4:</b> 2400-2500 MHz, 4 dBi &amp; 5000-6000 MHz, 5 dBi <b>Cable 5 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p> <p>LLPWG508 (2x Global 5G LTE, 2x WiFi, GNSS) <b>Cable 1 &amp; 2:</b> 617-960 MHz, 3 dBi &amp; 1710-6000 MHz, 4 dBi <b>Cable 3 &amp; 4:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 5 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p> <p>LLPG602 (2x LTE/5G, 3x WiFi, GNSS) <b>Cable 1 &amp; Cable 2:</b> 694-3700 MHz, 0 dBi to 4 dBi <b>Cable 3, 4 and 5:</b> 2400-2500 MHz, 4 dBi &amp; 5000-6000 MHz, 5 dBi <b>Cable 6 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p> <p>LLPG702 (2x LTE/5G, 4x WiFi, GNSS) <b>Cable 1 &amp; Cable 2:</b> 694-3700 MHz, 0 dBi to 4 dBi <b>Cable 3, 4, 5 &amp; 6:</b> 2400-2500 MHz, 4 dBi &amp; 5000-6000 MHz, 5 dBi <b>Cable 7 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p>

# Multiband LTE/5G, WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx etc

	<p>LLPWG801 (2x Global 5G LTE, 4x WiFi, 2x GNSS) <b>Cables 1&amp;2 (5G LTE):</b> 617-960 MHz, 2 dBi &amp; 1710-6000 MHz, 5 dBi <b>Cables 3-6 (WiFi):</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 7&amp;8 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 22.8cm L x 8.9cm W x 3.18cm H Configurable cable lengths and connector types</p>
---	---

	<p>LTMG944<sup>(M)</sup> (4x LTE/5G, 4x WiFi, GNSS) <b>Cables 1-4:</b> 694-960 MHz, 2 dBi &amp; 1710-3700 MHz, 5 dBi <b>Cables 5-8:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 9:</b> 1561, 1575, &amp; 1602 MHz, 5dBi Thru Hole Mount Dimensions: 13.9 cm Dia. x 6.0 cm H Configurable cable lengths and connector types</p> <p>LTM943 : 4xLTE/5G, 3xWiFi, 1xGPS <b>Cable 1-4:</b> 694-960 MHz, 2 dBi &amp; 1710-3700 MHz, 5 dBi <b>Cable 5-7:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 8 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 13.9 cm Dia. x 6.0 cm H Configurable cable lengths and connector types</p> <p>LTM942 : 4xLTE/5G, 2xWiFi, 1xGPS <b>Cable 1-4:</b> 694-960 MHz, 2 dBi &amp; 1710-3700 MHz, 5 dBi <b>Cable 5-6:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 7 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 13.9 cm Dia. x 6.0 cm H Configurable cable lengths and connector types</p> <p>LTM941 : 4xLTE/5G, 1xWiFi, 1xGPS <b>Cable 1-4:</b> 694-960 MHz, 2 dBi &amp; 1710-3700 MHz, 5 dBi <b>Cable 5:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 6 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 13.9 cm Dia. x 6.0 cm H Configurable cable lengths and connector types</p> <p>LTMG401<sup>(M)</sup> (2x LTE, 1x WiFi, GNSS) <b>Cable 1 &amp; 2:</b> 694-960 MHz, 3 dBi &amp; 1710-2170 MHz, 4 dBi <b>Cable 3:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 4 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 5 dBi Thru Hole Mount Dimensions: 13.9 cm Dia. x 6.0 cm H Configurable cable lengths and connector types</p>
---	---

# Multiband LTE/5G, WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx



LTMG402<sup>(M)</sup> (2x LTE/5G, 1x WiFi, GNSS)

**Cable 1 & 2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4 dBi

**Cable 3:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 4 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi  
Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG408<sup>(M)</sup> (2x Global 5G LTE, 1x WiFi, GNSS)

**Cables 1 & 2:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 4 dBi

**Cable 3:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 4 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi  
Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG501<sup>(M)</sup> (2x LTE, 2x WiFi, GNSS)

**Cable 1 & 2:** 694-960 MHz, 3 dBi & 1710-2170 MHz, 4 dBi

**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi  
Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG502<sup>(M)</sup> (2x 4G/5G Cellular, 2x WiFi, GNSS)

**Cable 1 & 2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4 dBi

**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi  
Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG505<sup>(M)</sup> (1x LTE, 3x WiFi, 1x GNSS)

**Cable 1:** 694-960 MHz, 3 dBi & 1710-2170 MHz, 4 dBi

**Cable 2-4:** 2400-2500 MHz & 4900-6000 MHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG508<sup>(M)</sup> (2x Global 5G LTE, 2x WiFi, GNSS)

**Cable 1 & 2:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 4 dBi

**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi  
Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

# Multiband LTE/5G, WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx



LTMG601<sup>(M)</sup> (2x LTE, 3x WiFi, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-2170 MHz, 4dBi

**Cable 3-5:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG602<sup>(M)</sup> (2x LTE/5G, 3x WiFi, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4dBi

**Cable 3-5:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG608<sup>(M)</sup> (2x Global 5G LTE, 3x WiFi, GNSS)

**Cables 1 & 2:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 4 dBi

**Cables 3 - 5:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG610<sup>(M)</sup> (2x Global 5G LTE, 3x WiFi, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-6000 MHz, 5dBi

**Cable 3-5:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG702<sup>(M)</sup> (2x LTE/5G, 4x WiFi, GNSS)

**Cable 1&2:** 694-960 MHz, 3 dBi & 1710-3700 MHz, 4dBi

**Cable 3-6:** 2.4-2.5 & 4.9-6.0 GHz, 5dBi

**Cable 7 (GNSS):** 1561, 1575, & 1602 MHz, 5dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG708<sup>(M)</sup> (2x Global 5G LTE, 4x WiFi, GNSS)

**Cables 1 & 2:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 4 dBi

**Cables 3 - 6:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 7 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

# Multiband LTE/5G, WiFi & GNSS

**(M)** Magnetic mount option also available with side entry cables. Replace part number LTMGxxx with MLTMGxxx



LTMG942<sup>(M)</sup> (4x LTE, 2x WiFi, GNSS)

**Cable 1-4:** 694-960 MHz, 2 dBi & 1710-3700 MHz, 5 dBi

**Cable 5-6 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 7 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG944<sup>(M)</sup> (4x LTE/5G, 4x WiFi, GNSS)

**Cables 1-4 (LTE):** 694-960 MHz, 2 dBi & 1710-3700 MHz, 5 dBi

**Cables 5-8 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 9 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG943<sup>(M)</sup> 4xLTE, 3xWiFi, 1xGNSS

**Cable 1-4:** 694-960 MHz, 2 dBi & 1710-3700 MHz, 5 dBi

**Cable 5-7 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 8 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMG941<sup>(M)</sup> 4xLTE, 1xWiFi, 1xGNSS

**Cable 1-4:** 694-960 MHz, 2 dBi & 1710-3700 MHz, 5 dBi

**Cable 5 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMWG944 (4x Global 5G LTE, 4x WiFi, GNSS)

**Cables 1-4 (5G):** 617-960 MHz, 2 dBi & 1710-6000 MHz, 5 dBi

**Cables 5-8 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 9 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

LTMWG943 (4x5G, 3xWiFi, 1xGNSS)

**Cables 1-3 (5G):** 617-960 MHz, 2 dBi & 1710-6000 MHz, 5 dBi

**Cables 4-7 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 8 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi

Thru Hole Mount

Dimensions: 13.9 cm Dia. x 6.0 cm H

Configurable cable lengths and connector types

# Multiband LTE/5G, WiFi & GNSS



LTMWG942 4x5G, 2xWiFi, 1xGNSS  
**Cables 1-3 (Sub-6 5G Cellular):** 617-960 MHz, 2 dBi & 1710-6000 MHz, 5 dBi  
**Cables 4-6 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi  
**Cable 7 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi  
Thru Hole Mount  
Dimensions: 13.9 cm Dia. x 6.0 cm H  
Configurable cable lengths and connector types

LTMWG941 (4x5G, 1xWiFi, 1xGNSS)  
**Cables 1-3 (Sub-6 5G Cellular):** 617-960 MHz, 2 dBi & 1710-6000 MHz, 5 dBi  
**Cables 4 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi  
**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz, 5 dBi  
Thru Hole Mount  
Dimensions: 13.9 cm Dia. x 6.0 cm H  
Configurable cable lengths and connector types



MXFG702 (1x LTE/5G, 4x WiFi, 1x GNSS)  
**Cables 1&2:** 694-960 MHz/1710-3700 MHz  
**Cables 3-6:** 2.4-2.5 GHz/ 4.9-6 GHz  
**Cable 7 (GNSS):** 1561, 1575, & 1602 MHz  
Thru Hole Mount  
Dimensions: 19cm x 5.7cm x 6.4cm  
Configurable cable lengths and connector types

MXFG602: 2xLTE, 3xWiFi, 1xGNSS  
**Cables 1&2:** 694-960 MHz/1710-3700 MHz  
**Cables 3-5:** 2.4-2.5 GHz/ 4.9-6 GHz  
**Cable 6 (GNSS):** 1561, 1575, & 1602 MHz  
Thru Hole Mount  
Dimensions: 19cm x 5.7cm x 6.4cm  
Configurable cable lengths and connector types

MXFG502: 2xLTE, 2xWiFi, 1xGNSS  
**Cables 1&2:** 694-960 MHz/1710-3700 MHz  
**Cables 3-4:** 2.4-2.5 GHz/ 4.9-6 GHz  
**Cable 5 (GNSS):** 1561, 1575, & 1602 MHz  
Thru Hole Mount  
Dimensions: 19cm x 5.7cm x 6.4cm  
Configurable cable lengths and connector types

MXFG402: 2xLTE, 1xWiFi, 1xGNSS  
**Cables 1&2:** 694-960 MHz/1710-3700 MHz  
**Cables 3:** 2.4-2.5 GHz/ 4.9-6 GHz  
**Cable 4 (GNSS):** 1561, 1575, & 1602 MHz  
Thru Hole Mount  
Dimensions: 19cm x 5.7cm x 6.4cm  
Configurable cable lengths and connector types



# Multiband LTE/5G, WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number SMWGxxx with MGWGxxx



SMWG-305<sup>(M)</sup> (1x LTE, 1x WiFi, 1x GNSS)

**Cable 1:** 694-894 MHz, 3 dBi & 1.70-2.7 GHz, 5 dBi

**Cable 2:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi gain  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H

Configurable cable lengths and connector types

SMWG-306<sup>(M)</sup> (1x WiFi, 1x Telstra 5G/DSRC, 1x GNSS)

**Cable 1:** 2.4-2.5, 5 dBi

**Cable 2:** 3.0-6.0 GHz, 5 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi gain  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H

Configurable cable lengths and connector types

SMWG-311<sup>(M)</sup> (1x LTE/5G, 1x WiFi, 1x GNSS)

**Cable 1:** 694-960 MHz, 3 dBi & 1.7-3.7 GHz, 4 dBi

**Cable 2 (WiFi):** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi gain  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H

Configurable cable lengths and connector types

SMWG-312<sup>(M)</sup> (1x Global LTE/5G, 1x WiFi, 1x GNSS)

**Cable 1:** 694-960 MHz, 3 dBi & 1710-6000 MHz, 5 dBi

**Cable 2:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 3 (GNSS):** 1561, 1575, & 1602 MHz,  
LNA: 26dB, 5 dBi nominal RHCP  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H

Configurable cable lengths and connector types

SMWG-412<sup>(M)</sup> (1x LTE, 2x WiFi, 1x GNSS)

**Cable 1:** 694-894 MHz, 3 dBi & 1.70-2.7 GHz, 5 dBi

**Cable 2:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 3:** 2.1-2.5 & 4.4-6.0 GHz, 5 dBi

**Cable 4 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi gain  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H

Configurable cable lengths and connector types

SMWG-414<sup>(M)</sup> (1x LTE/5G, 2x WiFi, 1x GNSS)

**Cable 1:** 694-894 MHz, 3 dBi & 1.70-3.7 GHz, 5 dBi

**Cable 2:** 2.4-2.5 & 4.9-6.0 GHz, 5 dBi

**Cable 3:** 2.1-2.5 & 4.4-6.0 GHz, 5 dBi

**Cable 4 (GNSS):** 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi gain  
Thru Hole Mount

Dimensions: 10.7cm Dia. x 8.1cm H




Configurable cable lengths and connector types

# Multiband LTE/5G, WiFi & GNSS

(M) Magnetic mount option also available with side entry cables. Replace part number SMWGxxx with MGWGxxx

	<p>SMWG-415<sup>(M)</sup> (1x LTE, 1x WiFi, 2x GNSS) <b>Cable 1:</b> 694-960 MHz, 3 dBi &amp; 1710-2700 MHz, 5 dBi <b>Cable 2:</b> 2.4 &amp; 4.9-6.0 GHz, 5 dBi <b>Cable 3 &amp; 4 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, LNA 26 dB, 5 dBi gain Thru Hole Mount Dimensions: 10.7cm Dia. x 8.1cm H Configurable cable lengths and connector types</p>
	<p>GL7X1-IOTCM-5FT (4x Global 5G LTE, 2x WiFi, 1x GNSS) <b>Cable 1 thru 4:</b> 617-960 MHz, 3 dBi &amp; 1710-6000 MHz, 4 dBi <b>Cable 5&amp;6:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 6dBi <b>Cable 5 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB Thru Hole Mount Dimensions: 251 x 88 mm Configurable cable lengths and connector types</p>
	<p>GL9X1AX-SF (4x Global 5G LTE, 4x WiFi, 1x GNSS) <b>Cable 1 thru 4:</b> 617-960 MHz, 2 dBi &amp; 1710-6000 MHz, 5 dBi <b>Cable 5 thru 8:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 9dBi <b>Cable 9 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB Thru Hole Mount Dimensions: 17.6cm Lx 15.48cm W x 7.65 H cm Configurable cable lengths and connector types</p> <p>GL7X1AX-SF (4x Global 5G LTE, 2x WiFi, 1x GNSS) <b>Cable 1 thru 4:</b> 617-960 MHz, 2 dBi &amp; 1710-6000 MHz, 5 dBi <b>Cable 5 &amp; 6:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 9dBi <b>Cable 7 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB Thru Hole Mount Dimensions: 17.6cm Lx 15.48cm W x 7.65 H cm Configurable cable lengths and connector types</p> <p>GL6X1AX-SF (2x LTE/5G, 3x WiFi, 1x GNSS) <b>Cable 1 &amp; 2:</b> 600-960 MHz, 3 dBi &amp; 1710-3800 MHz, 6 dBi <b>Cable 3, 4 &amp; 5:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 9dBi <b>Cable 6 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB Thru Hole Mount Dimensions: 13.0cm Dia. x 9.2cm W Configurable cable lengths and connector types</p> <p>GL125-DLTEMIMO (2x LTE/5G, 2x WiFi, 1x Multi GNSS - L1, L2, L5) <b>Cable 1 &amp; 2:</b> 600-960 MHz, 2.5 dBi &amp; 1710-3800 MHz, 6 dBi <b>Cable 3 &amp; 4:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 6dBi <b>Cable 5 (GNSS):</b> 1150-1290 MHz, 1500-1615 MHz, 28 dB Thru Hole Mount Dimensions: 13.0cm Dia. x 9.2cm W Configurable cable lengths and connector types</p>

# Multiband LTE/5G, WiFi & GNSS

	<p>GLHPDLTEMIMO-SF (2x LTE, 2x WiFi, 1 x GNSS)  <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi  <b>Cable 3 &amp; 4:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 4 dBi  <b>Cable 5 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimensions: 13.6 Dia. x 8.97cm H                      Configurable cable lengths and connector types</p> <p>GLHPDLTE-SF (2x LTE, 3x WiFi, 1 x GNSS)  <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi  <b>Cable 3, 4, 5:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 4 dBi  <b>Cable 6 (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimensions: 13.6 Dia. x 8.97cm H                      Configurable cable lengths and connector types</p>
	<p>GNSS4GBTSM (1x LTE, 1x WiFi, 1x GNSS)  <b>Cable 1:</b> 698-960 MHz, 5 dBi &amp; 1710-2700 MHz, 5 dBi  <b>Cable 2:</b> 2.4 - 2.5 GHz, 3dBi  <b>Cable 3:</b> (GNSS): 1561, 1575, &amp; 1602 MHz, 28 dB                      Thru Hole Mount                      Dimensions: 8cm OD x 1.5cm H                      Configurable cable lengths and connector types</p>
	<p>TRP-20INT-5-B (2x Global 5G LTE, 2x WiFi, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 617-960 MHz, 5 dBi &amp; 1710-6000 MHz, 8 dBi  <b>Cable 3 &amp; 4:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 9 dBi  <b>Cable 5: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimesnions: 10.3cm W x 7cm L x 11.9cm H                      Configurable cable lengths and connector types</p> <p>TRP-20INT-6-B (2x Global 5G LTE, 3x WiFi, 1x GNSS)  <b>Cable 1 &amp; 2:</b> 617-960 MHz, 5 dBi &amp; 1710-6000 MHz, 8 dBi  <b>Cable 3 to 5:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 9 dBi  <b>Cable 6: (GNSS):</b> 1561, 1575, &amp; 1602 MHz, 26 dB                      Thru Hole Mount                      Dimesnions: 10.3cm W x 7cm L x 11.9cm H                      Configurable cable lengths and connector types</p>

# Multiband LTE/5G, WiFi & GNSS



GL9X1AX-TRB (4x Global 5G LTE, 4x WiFi, 1x GNSS)  
**Cable 1 to 4:** 617-960 MHz, 3 dBi & 1710-6000 MHz, 5 dBi  
**Cable 5 to 8:** 2.4-2.5 & 4.9-6.0 GHz, 3 dBi  
**Cable 5: (GNSS):** 1561, 1575, & 1602 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 26.7cm L x 11.7cm W x 9.0cm H  
Configurable cable lengths and connector types



GLHPDLTEMIMO-LTB-S (2x LTE, 2x WiFi, 1x GNSS)  
**Cable 1 & 2:** 698-960 MHz, 2.5 dBi & 1710-2700 MHz, 2.5 dBi  
**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 4 dBi  
**Cable 5: (GNSS):** 1561, 1575, & 1602 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 10.3cm W x 8.8cm H  
Configurable cable lengths and connector types

GLLTEWIFI-TB (1x LTE, 1x WiFi, 1x GNSS)  
**Cable 1:** 698-960 MHz, 2.5 dBi & 1710-2700 MHz, 2.5 dBi  
**Cable 2:** 2.4-2.5 & 4.9-6.0 GHz, 4 dBi  
**Cable 3: (GNSS):** 1561, 1575, & 1602 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 10.3cm W x 8.8cm H  
Configurable cable lengths and connector types


GLHPDLTEMIMO-LTB (2x Global 5G LTE, 2x WiFi, 1x GNSS)  
**Cable 1 & 2:** 617-960 MHz, 4 dBi & 1710-6000 MHz, 8 dBi  
**Cable 3 & 4:** 2.4-2.5 & 4.9-6.0 GHz, 9 dBi  
**Cable 5: (GNSS):** 1561, 1575, & 1602 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 10.3cm W x 8.8cm H  
Configurable cable lengths and connector types


GLHPDM3-LTB (2x Global 5G LTE, 3x WiFi, 1x GNSS)  
**Cable 1 & 2:** 617-960 MHz, 4 dBi & 1710-6000 MHz, 8 dBi  
**Cable 3 to 5:** 2.4-2.5 & 4.9-6.0 GHz, 9 dBi  
**Cable 6: (GNSS):** 1561, 1575, & 1602 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 10.3cm W x 8.8cm H  
Configurable cable lengths and connector types



GPSHPMIMO-LTB (1x LTE, 2x WiFi, 1x GNSS)  
**Cable 1:** 698-960 MHz, 2.5 dBi & 1710-2700 MHz, 2.5 dBi  
**Cable 2 & 3:** 2.4-2.5 & 4.9-6.0 GHz, 2.5 dBi  
**Cable 4: (GPS):** 1575 MHz, 26 dB  
Thru Hole Mount  
Dimensions: 13cm W x 9.2cm H  
Configurable cable lengths and connector types

# Multiband LTE/5G, WiFi & GNSS

	<p>GNSMB-COV (2x LTE, 1x WiFi, 1x GNSS) Covert Antenna <b>Cable 1 &amp; 2:</b> 698-960 MHz, 2.5 dBi &amp; 1710-2700 MHz, 2.5 dBi <b>Cable 3:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 4 dBi <b>Cable 4:</b> (GNSS): 1561, 1575, &amp; 1602 MHz, 26 dB Tape Mount Dimensions: 15.1cm L x 13.2cm W x 2.5cm H Configurable cable lengths and connector types</p>
--	---

	<p>Aw-10 (1x LTE, 2x WiFi, 1x GNSS) <b>Cable 1:</b> 698-960 MHz, 1.5 dBi &amp; 1710-2700 MHz, 2.5 dBi <b>Cable 2 &amp; 3:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 1 dBi <b>Cable 4:</b> (GNSS): 1575, &amp; 1602 MHz, 27 dB Thru Hole Mount Dimensions: 10.2cm Dia. x 4.35cm H Configurable cable lengths and connector types</p> <p>Aw-10T-DLW (2x LTE, 2x WiFi, 1x GNSS) <b>Cable 1 &amp; 2:</b> 698-960 MHz, 1.5 dBi &amp; 1710-2700 MHz, 2.5 dBi <b>Cable 3 &amp; 4:</b> 2.4-2.5 &amp; 4.9-6.0 GHz, 1 dBi <b>Cable 5:</b> (GNSS): 1575, &amp; 1602 MHz, 27 dB Thru Hole Mount Dimensions: 10.2cm Dia. x 4.35cm H Configurable cable lengths and connector types</p>
--	--



*ENGINEERED FOR REAL TIME*

**Contact us:**

StepGlobal  
Unit 7, 444 Warrigal rd  
Heatherton, Vic, 3202  
Ph: 03 9551 7334

[stepglobal.com](http://stepglobal.com)  
[shop.stepglobal.com](http://shop.stepglobal.com)

[Home](#)