

GATEWAY & ANTENNA

Match-Up Guide

This Guide shows Mobile Mark Antennas that are COMPATIBLE with your



Gateway!



KONA MICRO LITE GATEWAY



PSKN3-925S



PSTG0-915SE



PSTG0-925HKS



PSTG0-868SE



PSKN3-900S



PSTG0-900HKS

GATEWAY & ANTENNA

Match-Up Guide

This Guide shows Mobile Mark Device Antennas that are COMPATIBLE with your



Kona Micro Lite IoT Gateway



	ISM EU868 Band 863 - 870 MHz	ISM NA915 Band 902 - 928 MHz
	EU Band	NA Band
North America Options		
PSKN3-925S (870 - 960 MHz)		√
PSTG0-915SE (902 - 928 MHz)		√
PSTG0-925HKS (870 - 960 MHz)		√
European Options		
PSKN3-900S (824 - 894 MHz)	√	
PSTG0-868SE (863 - 870 MHz)	√	
PSTG0-900HKS (824 - 894 MHz)	√	

ANTENNA CONNECTION NOTES:
Gateway has a Female SMA Jack (Female) Connection, All Antennas above provide the SMA Plug (Male) Connection.
Minimum quantities may apply, check with sales rep for lead times and MOQ.